



Certificate

of Conformity

LOVAG-Certificate No.: FR15-011

Certified Original Copy

This Certificate applies only to the apparatus verified. The responsibility for conformity of

any apparatus having the same

designation with that verified

responsible vendor.

rests with the manufacturer or

This certificate has been pre-

(Low Voltage Agreement Group) Objectives and Operating Prin-

pared according to LOVAG

ciples of mutual recognition.

The responsible certification body as a member of LOVAG issues a Certificate of Confor-

mity with the above mentioned

Only integral reproduction of

performed and the assigned

rated characteristics of the apparatus verified, are

permitted without written permission from the LOVAG Signatory responsible for this

Certificate

this Certificate or reproductions of this page accompanied by any page(s) on which are

Standard(s) following the

exclusive use of LOVAG

Verification instruction

stated the verifications

wherever applicable.

Apparatus

Remotely operated transfer switching equipment

Designation Type

ATyS, ATyS r, ATyS d, ATyS t, ATyS p, ATyS g: 1250 A, 2000 A, 3200 A

Manufacturer

SOCOMEC S.A. 1 - 4 Route de Westhouse - B.P. 60010 67235 BENFELD Cedex - France

Applicant:

SOCOMEC S.A. 1 Route de Westhouse - B.P. 60010 67235 BENFELD Cedex - France

Verified by:

ASEFA platform H01

The apparatus, constructed in accordance with the description mentioned in the Report listed in this Certificate has been subjected to the series of proving verifications in accordance with IEC 60947-6-1 (2013) Edition 3.1, EN 60947-6-1 (2006) + A1 (2014): Test sequence II

The results are shown in the Report in accordance to LOVAG. The values obtained and the general performance are considered to comply with the above Standard(s) and to justify the characteristics assigned by the manufacturer as stated below

Class PC					
415 V a.c.	Insulation voltage, Ui		1000 V		
50 / 60 Hz	Impu	Impulse withstand voltage, U _{imp} 1		12 kV	
1250 A		2000 A	3200 A	3200 A	
1250 A		2000 A	3200 A	3200 A	
AC-33B: 1250 A / 415 V ~		AC-32B: 2000 A / 415 V ~		AC-31B: 3200 A / 415 V ~	
	415 V a.c. 50 / 60 Hz 1250 A 1250 A AC-33B:	415 V a.c. Insul 50 / 60 Hz Impu 1250 A 1250 A AC-33B:	415 V a.c. Insulation voltage, U _i 50 / 60 Hz Impulse withstand voltage 1250 A 2000 A 1250 A 2000 A AC-33B: AC-32B:	415 V a.c. Insulation voltage, U _i 50 / 60 Hz Impulse withstand voltage, U _{imp} 1250 A 2000 A 3200 A 1250 A 2000 A 3200 A AC-33B: AC-32B: AC-31B	

This document includes

Test Report No.: H01.15.11 Issue Date: 2015-01-15

Responsible Certification Body:

Accréditation n°5-0037 Portée disponible sur /Scope available on www.cofrac.fr

ASEFA

33, avenue du Général Leclerc 92260 Fontenay-aux-Roses France

Marie-Elisabeth d'ORNANO

Authorized Signature Date: 2015-04-13